

### **AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application:

#### **Listing of Claims:**

- 1-17. (Canceled)
18. (Previously Presented) An apparatus for inserting an electrode into a myocardium of the heart, the apparatus comprising:
- an anchor configured to penetrate the myocardium in a first orientation and to anchor against an outside surface of the heart in a second orientation;
  - a tension element having a proximal end and a distal end, the distal end fastened to the anchor; and
  - an electrode having an inner guide channel to accommodate the tension element and having a pole at an end adapted for stimulating the myocardium, the electrode and the tension element configured such that the electrode can be threaded over the proximal end of the tension element and slideably advanced over the tension element towards the anchor during implantation, the guide channel having a proximal opening adapted to allow the proximal end of the tension element to exit therethrough;
- wherein the anchor and the tension element are configured to couple to the electrode, thereby chronically retaining the distal end of the electrode in the heart after implantation.
19. (Previously Presented) The apparatus of claim 18 further comprising:
- a tool for inserting the anchor through the myocardium to an operating position; and
  - a receiver tube for pre-forming a canal through the myocardium, the tube defining a lumen adapted to hold the anchor and the tool during insertion into the heart.
20. (Canceled)

21. (Previously Presented) The apparatus of claim 19 wherein the anchor includes an attachment area having a receiving aperture disposed at a trailing end of the anchor for fittingly receiving the tool.
22. (Previously Presented) The apparatus of claim 18 wherein the anchor further comprises at least one element having a position for deployment into the myocardium and an expanded position at the operating position.
23. (Withdrawn) The apparatus of claim 22 wherein a spring force biases the at least one element to the expanded operating position.
24. (Previously Presented) The apparatus of claim 19 wherein the anchor is rod-shaped having a first end and a second end and includes an attachment area comprising a longitudinal opening at the first end for receiving the tool and wherein the tension element is attached to the anchor between the first end and the second end.
25. (Previously Presented) The apparatus of claim 24 wherein the tension element is attached to the anchor at a location between the center of the anchor and a leading end.
26. (Withdrawn) The apparatus of claim 18 wherein the anchor is disk-shaped and the attachment area is a radially-oriented aperture in the anchor adapted for receiving the tool.
27. (Withdrawn) The apparatus of claim 18 wherein the anchor has a first angled leg and a second angled leg, the first leg having an aperture forming the attachment area for receiving the tool.
28. (Withdrawn) The apparatus of claim 18 wherein the anchor further comprises:
  - a central leg;
  - at least two outer legs; and
  - a membrane stretched between the central leg and the outer legs.
29. (Withdrawn) The apparatus of claim 18 wherein the anchor includes a plurality of legs defining a star-shape and the attachment area is an aperture in one of the legs adapted for receiving the tool.

30. (Withdrawn) The apparatus of claim 18 wherein the anchor has a plurality of leaves defining a cloverleaf-shape and the attachment area is an aperture adapted for receiving the tool and is disposed between two of the individual leaves.

31. (Previously Presented) The apparatus of claim 19 wherein the tool is a thin, flexible stylet.

32. (Canceled)

33. (Previously Presented) The apparatus of claim 18 wherein the proximal opening from the guide channel is disposed at a connection point such that the tension element is attachable to the electrode.

34. (Previously Presented) The apparatus of claim 33 wherein the proximal opening for the tension element is closed by a medical adhesive.

35. (Previously Presented) The apparatus of claim 33 wherein the connection point includes a fastening element for attaching the tension element to the electrode.

36. (Previously Presented) The apparatus of claim 33 wherein the tension element includes a stop located at a distance from the anchor for fixing the electrode to prevent movement in either of a forward or a rearward direction.

37. (Previously Presented) The apparatus of claim 36 wherein the stop comprises a thickening on the tension element having a diameter which exceeds an inner diameter of the guide channel.

38. (Previously Presented) The apparatus of claim 18 wherein the pole includes an anode spaced apart from a cathode.

39. (Previously Presented) The apparatus of claim 18 further comprising a first and a second electrode branching from a common supply lead, each electrode having an inner guide channel sized to accommodate a first and a second tension element, respectively, and each electrode having a pole at an end adapted for stimulating the myocardium.

40. (Previously Presented) The apparatus of claim 39 wherein the proximal opening from the guide channel is disposed near the branch of the supply lead.

41. (Previously Presented) The apparatus of claim 40 wherein the tension elements extend through the guide channels and are knotted together outside the proximal opening.

42. (Previously Presented) The apparatus of claim 39 further comprising an anode positioned on the common supply lead and a cathode positioned on each of the first and second electrodes.

43. (Previously Presented) An apparatus for inserting an electrode into a myocardium of the heart, the apparatus comprising:

an anchor configured to advance into and through the myocardium and to anchor against

an outside surface of the heart, said anchor having an attachment area;

a tension element having a proximal end and a distal end, the distal end structurally

independent from and fastened to the anchor; and

a first electrode having an inner guide channel, wherein the tension element and first

electrode are configured such that the electrode can be threaded over the proximal

end of the tension element and slideably advanced over the tension element

toward the anchor during implantation and having a pole near a distal end adapted

for stimulating the myocardium;

wherein the guide channel has a proximal opening adapted to allow the proximal end of

the tension element to exit therethrough.

44. (Previously Presented) The apparatus of claim 43 further comprising a tool detachably coupled to the attachment area for inserting the anchor through the myocardium to an operating position.

45. (Previously Presented) The apparatus of claim 44 further comprising a receiver tube for creating a canal through the myocardium, the receiver tube defining a lumen sized for holding the anchor and the tool during insertion into the heart.

46. (Canceled)

47. (Canceled)

48. (Previously Presented) The apparatus of claim 43 wherein the pole includes an anode spaced apart from a cathode.

49. (Previously Presented) The apparatus of claim 43 further comprising a second electrode having an inner guide channel to accommodate the tension element and having a pole at an end for stimulating the myocardium, the second electrode branching from a common supply lead with the first electrode.

50. (Previously Presented) An apparatus for inserting an electrode into a myocardium of a heart, the apparatus comprising:

- a tension element having a proximal end and a distal end;

- an electrode having an inner guide channel, wherein the tension element and electrode are configured such that the electrode can be threaded over the proximal end of the tension element and slideably advanced over the tension element towards the heart during implantation and having a pole at an end for stimulating the myocardium, the guide channel having a proximal opening adapted to allow the proximal end of the tension element to exit therethrough; and

- means for anchoring a distal end of the tension element within the myocardium, the means for anchoring structurally independent from and attached to the distal end of the tension element and configured to penetrate the myocardium and anchor against an outside surface of the heart.

Claims 51-65 (Canceled).